

Werktuigslijpmachines



EWAG RS-15

Machine occasion

N° de stock : **DB30207**



Jaar	2000
Vermogen op hoofdspil	2.2

Spindelsnelheid	1000 - 8000
X-as slag	490
Y-as slag	130
Z-as slag	115
Spanentransporteur	260
Kegel van de spindel van het werkstuk	HSK 63
Feeding	3 x 400 V
Formaten	1700x1750x1840
Gewicht	1850

Equipment:

Cross table KS15/60-002 – ref EWAG : 115-2-30692
 Grinding spindle with variable speed – ref EWAG : 115-2-29075
 Stepless adjustable oscillation device OR15 – ref EWAG : 115-2-28129
 Grinding pressure regulator AV15 (contact pressure : 0-400 N) – ref EWAG : 115-2-28150
 Projector assembly metric PRO15M – ref EWAG : 115-2-28138
 Projector with screen Ø150 [mm] MARCEL AUBERT
 Pneumatical clamping for B axis (by foot pedal) : 40 [Nm]
 4 axes digital display RSF ELEKTRONIC DIG 15-4 – ref EWAG : 115-2-32146
 P axis : 0.001 [mm]
 X axis : 0.01 [mm]
 Z axis : 0.001 [mm]
 B axis : 0.01°
 Dressing attachment AD15 – ref EWAG : 115-2-31107
 Transmitted light illumination (with green filter)
 Inclined tooth angle grinding device AWS with dividing head HSK63, sine bar compensation and setting gauge compensation – ref EWAG : 115-2-31052
 x1 grinding wheel adaptor Q40-fix-OCS (33 mm) – ref EWAG : 115-2-16414
 Coolant unit K3P with filter cartridge (capacity : 100 [l] – 45 [l/min] at 0.5 bar)
 LED lamp 24 [V] – IP67
 x7 grinding wheels TYROLIT Skytec PCD Basic 150 x 40 x 40 [mm] – NEW never used
 x1 grinding wheel TYROLIT 125 x 25 x 40 [mm] – NEW never used
 Users and service manual (in French)
 Service manual for the tooth angle grinding device AWS (in French)











